

## Centre for Advisory and Testing Services (CATS-MIST) Military Institute of Science and Technology

**Compressive Strength of Concrete Blocks** 

**CATS** Reference

: 2376/36545-A/Con/09/2023

Date

: 26.09.2023

Client

: Maxcrete Limited

**Project Name** 

: Autoclave Aerated Concrete (AAC) Blocks

Sample Brought By

: Engr. Abu Mohammad Samsuddin, Assistant General Manager

Test Method

: ASTM C1386

Date of Receiving

: 19.09.2023

Sample

: AAC Block, Size: 600mm x 200mm x

Date of Test

: 26.09.2023

Quantity of Sample

: 06 Pcs

Sample Condition : Unsealed

Test Results:

SI No.	Sample ID	Sawed Length	Sawed Width	Thickness	Area	Crushing Load	Crushing Strength	
		mm	mm	mm	mm <sup>2</sup>	/ kN	MPa	psi
1	Block 1	101.0	100.0	100.0	10100	79.7	7.9	1140
2	Block 2	102.0	100.0	100.0	10200	77.3	7.6	1100
3	Block 3	102.0	100.0	100.0	10200	77.6	7.6	1100

Average Crushing Strength:

7.7 MPa

1120.0 psi

Standard Deviation:

0.1 MPa

20.0 psi

Strength Class (ASTM 1386: Table 1):

AAC-6

## Remarks:

- 1. All information displayed above (other than the test results) was provided by the client.
- 2. CATS-MIST did not verify whether the samples are representative or not.

Test Supervised By:

Md. Johidul Islam, PhD, Engrs

Instructor Class-A CE Department, MIST Mirpur Cantonment, Dhaka Countersigned By:

Khondaker Sakil Ahmed, PhD, PEng Lt Col & Associate Professor Department of Civil Engineering MIŜT, Mirpur Camonmen

Note: Samples as supplied to us have been tested in our laboratory. CATS-MIST does not have any responsibility as to the representative character of the samples required to be tested. It is recommended that samples to be sent in secure and sealed cover/packet/container under signature of the competent authority in order to fraudulent fabrication of test results. It is recommended to collect all test reports by duly authorized person and not by the contractor/supplier himself.